


“Stay Connected” with



Solar Power Components

a PennEngineering® Company



Heyco® -Tite Tear-Away Liquid Tight Cordgrips


Straight-Thru, PG Hubs with Integral Sealing Ring

The Ultimate in Liquid Tight Strain Relief Protection



CABLE DIAMETER RANGE				PART NO.				DESCRIPTION	PART DIMENSIONS															
Minimum		Maximum		Including Nylon Nut*		No Nut			A		B		C		D		E							
in.	mm.	in.	mm.	Black	Gray	Black	Gray	Clearance Hole Dia.	in.	mm.	Max. O.A. Length	in.	mm.	Thread Length	in.	mm.	Thickness	in.	mm.	Flat Size	in.	mm.		
PG Hubs																								
.170	4,3	.450	11,4	M3216-SM	M3217-SM	M4764-SM	M4765-SM	SMCG 13.5	.804	20,4	1.53	38,9	.41	10,4	.21	5,3	.98	24,9						
.260	6,6	.545	13,8	M3219-SM	M3220-SM	M4766-SM	M4767-SM	SMCG 16	.886	22,5	1.68	42,7	.44	11,2	.25	6,4	1.06	26,9						
.435	11,0	.705	17,9	M3222-SM	M3223-SM	M4768-SM	M4769-SM	SMCG 21	1.115	28,3	1.89	48,0	.52	13,2	.25	6,4	1.30	33,0						
.590	15,0	1.000	25,4	M3225-SM	M3226-SM	M4770-SM	M4771-SM	SMCG 29	1.470	37,3	2.23	56,6	.57	14,5	.30	7,6	1.73	43,9						
.875	22,2	1.260	32,0	M3204-SM	M3203-SM	M4774-SM	M4775-SM	SMCG 36	1.875	47,6	2.39	60,7	.47	11,9	.31	7,9	2.05	52,1						
1.230	31,2	1.560	39,6	M3212-SM	M3209-SM	M4742-SM	M4743-SM	SMCG 42	2.130	54,1	2.50	63,5	.48	12,2	.36	9,1	2.46	62,5						
1.450	36,8	1.730	43,9	M3281-SM	M3282-SM	M4776-SM	M4777-SM	SMCG 48	2.340	59,4	2.63	66,8	.50	12,7	.42	10,7	2.73	69,3						

*Nylon locknuts shipped unassembled.

- The **New Tear-Away** Liquid Tight Cordgrips install as a plug to keep rain, insects and air contaminants outside of an enclosure that is waiting at field installation sites or even within a manufacturing setting for a prolonged period of time.
- **Note:** UL Certifications apply only when used as a cordgrip, not as a plug; When used as a plug, we meet IPx8 @ 2.6 PSI for 24 hrs, and IPx5.
- Units remain internally clean and moisture free until cable installation as a Heyco standard, and market-leading Cable Gland with full functionality that you have come to expect.
- Simply puncture the gland edge with a flat-head screwdriver and Tear-Away the ID for cable pass through like a standard Heyco Cable Gland.
- **Integral Sealing Ring** ensures a superior seal at the clearance or threaded mounting hole location.
- Approved for **NEMA 4, 4X, 6 and 6P applications** with use of nylon locknuts.
- IP 68 rated.
- Cordgrips are made of nylon construction with TPE sealing glands that resist salt water, weak acids, gasoline, alcohol, oil, grease, and common solvents.
- Consult Heyco for Cordgrips molded in other colors.



Click here or scan for assembly instructions



Material	Nylon 6/6 with TPE Sealing Gland
Certifications (when used as Cordgrip)	<ul style="list-style-type: none"> UL Listed under Underwriters' Laboratories File E51579 Recognized under the Component Program of Underwriters' Laboratories File E51579 to both Canadian and U.S. requirements CS cRUUS Certified by the Canadian Standards Association File 93876
Flammability Rating	94V-2 Standard
Temperature Range	Static -40°F (-40°C) to 239°F (115°C) Dynamic -4°F (-20°C) to 212°F (100°C)
IP Rating	IP 68 (70 PSI, 5 BAR) (IPx8 @ 2.6 PSI for 24 hrs and IPx5, when used as plug)