



Heyco® -Tite Snap-In-2® Liquid Tight Cordgrips

Straight-Thru, Snap-In Hubs

For Panels from .062" (1,6 mm) to .125" (3,2 mm) Thick


The Ultimate in Liquid Tight Strain Relief Protection

**NO LOCKNUT
REQUIRED!**


- Easy installation—unique fingers securely snap into a range of panel thicknesses – up to .125" (3,2 mm) – with no tools or locknuts required.
- Sealing flange prevents sealing washer displacement due to water velocity to ensure a liquid tight IP 65 seal.
- Eliminate need for locknut or threaded hole to achieve liquid tight seal at panel; perfect for low clearance installation where locking nut access is limited.
- Ratchet design of sealing nut assembly provides superior anti-vibration and ensures a firm grip on the cable.
- Foam washer included.
- Rotation prevented when used in Double D mounting holes.
- For Double D Mounting Hole Punches, see page 4-30.
- Available in multiple sizes for flexible cord diameters ranging from .065" (1,7 mm) to .920" (23,4 mm).
- Widest range of approved cable diameters. Cable ranges listed are for the maximum IP 68 sealing range. Contact Heyco for UL approved 514B cable ranges.
- We recommend using the fitting with the smallest maximum diameter that will fit your application.
- Consult Heyco for cordgrips molded in other colors.

CABLE DIA. RANGE				PART NO.	DESCRIPTION	UL or IEC	PANEL DIMENSIONS					
Minimum		Maximum					Black	A Mounting Hole Dia.		B To Prevent Rotation		C Max. O.A. Length
in.	mm.	in.	mm.				in.	mm.	in.	mm.	in.	mm.
.065 .115	1,7 2,9	.210 .250	5,3 6,4	M3802 M3800	LTRSCG 500 LTSCG 500	UL	.500	12,7	.450	11,4	1.21	30,7
.065 .105	1,7 2,7	.230 .315	5,8 8,0	M3808 M3806	LTRSCG 625 LTSCG 625		UL	.625	15,9	.550	14,0	1.30
.069 .230	1,8 5,8	.250 .395	6,4 10,0	M3814 M3812	LTRSCG 750 LTSCG 750	UL	.750	19,1	.660	16,8	1.48	37,6
.095 .170	2,4 4,3	.260 .450	6,6 11,4	M3820 M3818	LTRSCG 875 LTSCG 875		UL	.875	22,2	.770	19,6	1.46
.180 .260	4,6 6,6	.440 .546	11,2 13,9	M3826 M3824	LTRSCG 1000 LTSCG 1000	UL	1.000	25,4	.875	22,2	1.62	41,1
.250 .485	6,4 12,3	.485 .709	12,3 18,0	M3838 M3836	LTRSCG 1125 LTSCG 1125		UL	1.125	28,6	1.000	25,4	1.75
.490 .590	12,4 15,0	.787 .920	20,0 23,4	M3844 M3842	LTRSCG 1250 LTSCG 1250	UL	1.250	31,8	1.125	28,6	2.05	52,1
.490 .590	12,4 15,0	.787 1.000	20,0 25,4	M3850 M3848	LTRSCG 1375 LTSCG 1375		UL	1.375	34,9	1.250	31,8	2.05

Standard color black.



SEALING FLANGE/
WASHER CONSTRUCTION



SUGGESTED
CLEARANCE HOLE
FOR NONTHREADED
MOUNTING

*Quick
Specs*

Material
Certifications

Nylon 6/6 w/Buna N or TPE Sealing Gland
UL Recognized under Components Program of Underwriters' Laboratories
File E51579

Flammability Rating
Temperature Range

CS Certified by Canadian Standard Association File 93876C
94V-2
Static -40°F (-40°C) to 239°F (115°C)
Dynamic -4°F (-20°C) to 212°F (100°C)
IP 65

IP Rating