

“Stay Connected” with



HEYware Products


a PennEngineering® Company



HEYClip™ Push Rivet-Arrow

WILL FIT THESE PANELS						PART NO.	DESCRIPTION	PART DIMENSIONS						
MOUNTING HOLE DIA.		ASSEMBLED PANEL THICKNESS						Black	A Length		B Head Height		C Head Diameter	
		Min.		Max.										
in.	mm.	in.	mm.	in.	mm.		in.	mm.	in.	mm.	in.	mm.		
.142	3,6	.08	2,0	.14	3,5	4400	PRA 142-079	.37	9,5	.06	1,6	.25	6,4	
		.14	3,5	.20	5,0	4401	PRA 142-138	.45	11,5					
		.20	5,0	.26	6,5	4402	PRA 142-197	.53	13,5					
.161	4,1	.08	2,0	.14	3,5	4403	PRA 161-079	.39	10,0	.07	1,8	.31	8,0	
		.14	3,5	.22	5,5	4404	PRA 161-138	.47	12,0					
		.22	5,5	.30	7,5	4405	PRA 161-217	.55	14,0					
.193	4,9	.08	2,0	.16	4,0	4406	PRA 193-079	.43	11,0	.09	2,2	.35	9,0	
		.16	4,0	.24	6,0	4407	PRA 193-157	.51	13,0					
		.24	6,0	.31	8,0	4408	PRA 193-236	.57	14,5					

- Designed for fast and easy installation with no tools – just fingertip pressure required.
- Simply place rivet into the hole and press down on the head to fasten; arrow shape flares to securely fasten components.
- To release, simply pull up on rivet head section.
- Round head provides a clean, finished look.



Material Nylon 6
 Flammability Rating UL 94V-2
 Temperature Range -22°F (-30°C) to 167°F (75°C)

*Quick
Specs*