

“Stay Connected” with



HEYware Products

a PennEngineering® Company






- Quick, easy installation is fast, saving time and money.
- Wide cable diameter range handles multiple applications.
- Material choices cover a number of application requirements for flammability and temperature.
- Releasable and reusable.
- Secure clamping will not release easily.
- Locking feature prevents twisting apart.




Heyco® Speed Bundle Clamps

BUNDLE DIAMETER				PART NO.			DESCRIPTION	PART DIMENSIONS						MOUNTING HOLE DIAMETER			
A		Natural	HS/UV Black	V-0 Black	Overall Height (closed)			Width		Depth		Hole Diameter					
Minimum	Maximum				in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.	mm.			
.29	7,4	.44	11,2	15250	15250B	15250F	SBC 437	.78	19,8	1.12	28,4			-	-		
.41	10,4	.69	17,5	15254	15254B	15254F	SBC 687	.97	21,8	1.24	31,5	.31	7,9	-	-		
.60	15,2	.88	22,2	15258	15258B	15258F	SBC 875	1.27	32,3	1.66	42,2			-	-		
.87	22,1	1.09	27,8	15260	15260B	15260F	SBC 1093	1.64	41,7	2.29	58,2			-	-		
1.10	27,9	1.50	38,1	15264	15264B	15264F	SBC 1500	2.25	57,2	3.05	77,5	.50	12,7	-	-		
1.37	34,5	2.00	50,8	15268	15268B	15268F	SBC 2000	2.50	63,5	3.46	87,6			-	-		
Push Mount																	
.29	7,4	.44	11,2	15360	15360B	15360F	SBCPM 437-187	.92	23,4	1.12	28,4				.187	4,8	
				15390	15390B	15390F	SBCPM 437-250								.250	6,4	
.41	10,4	.69	17,5	15364	15364B	15364F	SBCPM 687-187	1.05	26,7	1.24	31,5	.31	7,9			.187	4,8
				15394	15394B	15394F	SBCPM 687-250									.250	6,4
.60	15,2	.88	22,2	15368	15368B	15368F	SBCPM 875-187	1.40	35,6	1.66	42,2					.187	4,8
				15398	15398B	15398F	SBCPM 875-250									.250	6,4

SBC



SBCPM



PANEL THICKNESS Min. .031 (0,8 mm)
Max. .093 (2,4 mm)

Quick Specs

Material – Flammability Rating
 Natural Nylon 6/6 – UL 94 V-2
 Black Heat Stable / UV Stable Nylon – UL 94 V-2
 Black Nylon 6/6 – UL 94 V-0

Temperature Range
 32°F (0°C) to 185°F (85°C)
 -40°F (-40°C) to 239°F (115°C)
 -40°F (-40°C) to 185°F (85°C)